

Flankenoffen, formgezahnt



XPZ



XPA



XPB

Alle Schmalkeilriemen Rex sind nach Wirklänge Lw angegeben

XPZ			XPA			XPB	
Lw			Lw			Lw	
562	1012	1737	582	1500	3000	1250	6700
587	1037	1750	657	1507	3150	1320	5VX 560
592	1047	1762	682	1532	3350	1400	5VX 630
602	1060	1787	707	1557	3550	1450	5VX 710
612	1077	1800	732	1582	3750	1500	5VX 1500
622	1087	1887	757	1600	4000	1525	5VX 1600
630	1112	1900	782	1607		1550	5VX 1700
637	1120	1937	800	1632		1600	5VX 1800
662	1137	2000	807	1657		1650	5VX 1900
670	1152	2037	832	1682		1700	5VX 2000
682	1162	2120	850	1700		1750	
687	1180	2240	857	1707		1800	
697	1187	2360	882	1732		1900	
710	1202	2500	900	1757		1930	
717	1212	2650	907	1782		1950	
722	1237	2800	932	1800		2000	
737	1250	3000	950	1807		2020	
750	1262	3150	957	1832		2120	
762	1287	3350	982	1857		2180	
772	1312	3550	1000	1882		2240	
787	1320		1007	1900		2360	
800	1327		1012	1907		2410	
812	1337		1032	1932		2500	
825	1362		1042	1950		2530	
837	1387		1060	1957		2650	
850	1400		1082	1982		2680	
857	1412		1107	2000		2710	
562	1437		1120	2007		2800	
875	1462		1132	2032		2840	
887	1487		1157	2057		2900	
892	1500		1180	2082		3000	
900	1512		1207	2120		3150	
912	1437		1232	2132		3250	
917	1462		1250	2157		3350	
922	1487		1257	2182		3450	
925	1500		1282	2232		3550	
937	1512		1307	2240		3750	
947	1537		1320	2307		3800	
950	1562		1332	2360		4000	
957	1587		1357	2382		4250	
962	1600		1382	2432		4500	
967	1612		1400	2464		4750	
977	1637		1407	2482		5000	
987	1662		1432	2500		5300	
992	1687		1457	2650		5600	
1000	1700		1482	2800		6000	