




Unsere Bestell-Nr.	Handelsübliche Bezeichnung	DIN/ISO (oder sonstige Bezeichnung)	Teilung p mm	Lichte Weite b (mm)	Rollen-Ø D1 mm	Bolzen-Ø D2 mm	Lasch. dicke (max) mm	Mittenmaß e mm	Ges. breite G (max) mm	Gewicht q kg/m	Bruchlast (min) N
RK04B1	6 x 2,8 mm	# 04-B-1	6,0	2,8	4,0	1,85	0,65		7,4	0,12	3 000
RK05B1	8 x 3 mm	# 05-B-1	8,0	3,0	5,0	2,31	0,89		8,6	0,18	5 000
RK06B1	3/8" x 7/32"	# 06-B-1	9,525	5,72	6,35	3,28	1,41		13,5	0,41	9 000
RK08B1	1/2" x 1/8"	# 08-B-1	12,7	7,75	8,51	4,45	1,78		13,9	0,78	16 000
RKF83	1/2" x 3/16"	F83	12,7	4,88	7,75	3,66	1,15		10,2	0,28	8 200
RKF83V	1/2" x 3/16"	F83 V	12,7	4,88	7,75	3,66	1,46		11,2	0,33	9 200
RK083	1/2" x 3/16"	083-1	12,7	4,88	7,75	4,09	1,51		13,1	0,44	15 500
RK084	1/2" x 3/16"	084-1	12,7	4,88	7,75	4,09	1,96		12,9	0,42	12 000
RKS84V	1/2" x 1/4"	S84 V	12,7	6,4	7,75	3,97	1,63		14,5	0,59	16 000
RKL84	1/2" x 1/4"	L84	12,7	6,4	8,51	4,45	1,77		14,9	0,49	15 000
RK08B1	1/2" x 5/16"	# 08-B-1	12,7	7,75	8,51	4,45	1,78		15,4	0,67	19 600
RKS814	5/8" x 1/4"	M104	15,875	9,65	10,16	5,08	1,82		17,0	0,7	18 000
RK10B1	5/8" x 3/8"	# 10-B-1	15,875	9,65	10,16	5,08	1,82		19,4	0,95	22 700
RK12B1	3/4" x 7/16"	# 12-B-1	19,05	11,68	12,07	5,72	1,97		19,6	0,95	22 400
RK12B1V	3/4" x 7/16"	(12-14V)	19,05	11,68	12,07	6,1	2,8		22,7	1,25	29 000
RK34135	3/4" x 1 1/8"		19,05	13,5	12,07	5,72	3,0		25,0	1,56	43 000
RK11212	1" x 1 1/2" x 1/2"		25,4	12,7	12,70	6,98	2,5		28,6	1,65	35 000
RK11258	1" x 1 1/2" x 5/8"		25,4	12,7	15,88	8,28	3,10		26,2	1,38	20 000
RK16B1	1" x 17 mm	# 16-B-1	25,4	17,02	15,88	8,28	4,19		31,2	2,66	58 000
RK20B1	1 1/4" x 3/4"	# 20-B-1	31,75	19,56	19,05	10,19	4,72		36,1	2,7	60 000
RK24B1	1 1/2" x 1"	24-B-1	38,1	25,4	25,4	14,63	6,25		43,2	3,6	95 000
RK28B1	1 3/4" x 31 mm	28-B-1	44,45	30,99	27,94	15,90	7,76		53,4	6,7	180 000
RK32B1	2" x 31 mm	32-B-1	50,8	30,99	29,21	17,81	7,26		65,1	8,3	200 000
Zweifach-Rollenketten											
DRK05B2	8 mm x 3 mm	05-B-2	8,0	3,0	5,0	2,31	0,89	5,64	14,3	0,36	7 500
DRK06B2	3/8" x 7/32"	# 06-B-2	9,525	5,72	6,35	3,28	1,41	10,2	23,8	0,78	16 000
DRK08B2	1/2" x 5/16"	# 08-B-2	12,7	7,75	8,51	4,45	1,78	13,9	31,0	1,35	32 000
DRK10B2	5/8" x 3/8"	# 10-B-2	15,875	9,65	10,16	5,08	1,82	16,6	36,2	1,35	40 000
DRK12B2	3/4" x 7/16"	# 12-B-2	19,05	11,68	12,07	5,72	1,97	19,5	42,2	2,5	53 000
DRK16B2	1" x 17 mm	# 16-B-2	25,4	17,02	15,88	8,28	4,19	31,9	68,0	5,4	106 000
DRK20B2	1 1/4" x 3/4"	20-B-2	31,75	19,56	19,05	10,19	4,72	36,5	79,0	7,2	170 000
DRK24B2	1 1/2" x 1"	24-B-2	38,1	25,4	25,4	14,63	6,25	48,4	101,0	13,5	280 000
DRK28B2	1 3/4" x 31 mm	28-B-2	44,45	30,99	27,94	15,90	7,76	59,6	124,0	16,6	360 000
Dreifach-Rollenketten											
TRK06B3	3/8" x 7/32"	06-B-3	9,525	5,72	6,35	3,28	1,41	10,2	34,0	1,18	23 600
TRK08B3	1/2" x 5/16"	08-B-3	12,7	7,75	8,51	4,45	1,78	13,9	44,9	2,0	47 500
TRK10B3	5/8" x 3/8"	10-B-3	15,875	9,65	10,16	5,08	1,82	16,5	52,8	2,8	60 000
TRK12B3	3/4" x 7/16"	12-B-3	19,05	11,68	12,07	5,72	1,97	19,4	61,7	3,8	80 000
TRK16B3	1" x 17 mm	16-B-3	25,4	17,02	15,88	8,28	4,19	31,8	99,9	8	160 000
TRK20B3	1 1/4" x 3/4"	20-B-3	31,75	19,56	19,05	10,19	4,72	36,5	116,0	11	250 000
TRK24B3	1 1/2" x 1"	24-B-3	38,1	25,4	25,4	14,63	6,25	48,4	150,0	21	425 000

auch in rostfrei (Achtung: reduzierte Bruchkräfte) oder vernickelt
auch mit geraden Laschen (Zusatzbezeichnung GL)

