

Klassische Keilriemen

nach DIN 2215



5 x 3 mm



6 x 4 mm



8 x 5 mm



10 x 6 mm



13 x 8 mm

Alle klassischen Keilriemen sind nach Innenlänge Li angegeben

5 x 3 Li	6 x 4 Li	8 x 5 Li	10 x 6 Li		13 x 8 Li		
190	280	315	340	1060	407	1075	2100
229	300	355	355	1080	457	1090	2120
260	335	375	375	1100	480	1100	2134
280	400	400	400	1120	508	1105	2150
300	425	425	425	1132	535	1120	2160
315	450	450	450	1150	560	1143	2185
322	500	475	475	1165	575	1150	2200
335	540	500	480	1180	585	1168	2210
375	600	530	500	1194	600	1180	2220
425	850	545	508	1215	610	1190	2240
475		550	515	1225	620	1200	2260
500		560	525	1235	630	1215	2286
530		575	530	1250	635	1250	2360
554		580	540	1262	650	1270	2413
600		600	560	1270	660	1300	2438
		630	575	1295	670	1320	2464
		650	585	1320	686	1350	2500
		670	600	1346	700	1375	2540
		700	610	1365	710	1400	2591
		710	630	1371	730	1422	2650
		725	650	1400	750	1450	2667
		750	670	1422	767	1475	2725
		760	700	1435	775	1500	2743
		775	710	1450	787	1525	2770
		800	725	1475	800	1550	2800
		825	730	1500	813	1575	2845
		830	750	1524	825	1600	2895
		850	765	1550	841	1625	3000
		875	775	1575	850	1650	3048
		900	800	1600	863	1676	3150
		950	820	1626	875	1700	3250
		965	825	1651	889	1725	3550
		1000	838	1675	900	1750	3658
		1020	850	1700	914	1775	3750
		1050	865	1725	925	1800	4000
		1075	875	1750	940	1825	4250
		1120	900	1775	950	1854	4750
		1200	925	1800	965	1880	5000
		1250	950	1850	975	1900	
			975	1900	990	1930	
			980	1975	1000	1956	
			1000	2000	1016	1980	
			1016	2120	1030	2000	
			1030	2240	1041	2032	
			1041	2360	1050	2060	
			1050	2500	1060	2083	